



REVIVAL BYTY
- REZIDENCE ŽELIVSKÁ -

Apartment Standards



Bathroom Wall Tiles

Rako Dale suri 30x60 cm



Bathroom Wall and Floor Tiles

Tiles Kale Terrazzo white 60x60 cm



Flooring (Glued Vinyl)

KPP Dub Erica



Sink

Ideal Standard Strada 50x42 cm



Sink Faucet

Sink Faucet GROHE Start



Shower Faucet

Shower Faucet GROHE Cubeo



Shower Screen

Shower Screen Walk-in 115 cm



Bathroom Radiator

Combined radiator SAT KH 150x45 cm



Toilet

Floor-standing Jika Cubito



Interior Doors

Design:

Rebated with semi-rebate

Door fill:

acoustic particleboard (DTD)
(chipboard core with hollow frame construction)

Surface finish:

CPL (Continuous Pressure Laminate) – durable material made from laminate resin under high temperature,
CPL thickness 0.30 mm

Door hinges:

3x standard pivot, silver

Door frame:

Made from solid pressed MDF boards, providing the highest resistance to mechanical damage.
(In standard versions, particle board is used, which is prone to impact and cracking!)

Handles:

Brushed steel in silver color, highly resistant to mechanical damage (e.g., from rings on fingers), secured with a welded threaded nut – preventing loosening or sagging.

Lock:

WC/bathroom – rotary butterfly knob.
Rooms/hallway – standard room key.

Entrance Door

Manufacturer:

Solodor type: Security with fire resistance
DPO – RC2 – EI30 with certification compliant with fire safety regulations (PBŘ)

Design:

Rebated with semi-rebate
Surface finish: CPL (Continuous Pressure Laminate) – durable material made from laminate resin under high temperature,
CPL thickness 0.70 mm

Door fill:

Acoustic solid oak panel with foam filling,
noise reduction 37 dB

Lock:

three-point FAB with pins to prevent door wing removal

Door frame:

Metal fire-resistant, anchored into walls with poured concrete filling, certified compliant with fire safety regulations (PBŘ)

Handles:

Brushed cast steel in silver color, highly resistant to mechanical damage (e.g., from rings on fingers), secured with a welded threaded nut – preventing loosening or sagging.
Lock: standard construction cylinder FAB 35/40, 3 keys, no security card for subsequent replacement after move-in.

Electrical Completion Elements

ABB Levit® white



Apartment Ventilation Unit

Ventilation units FLUO LOCAL 02

